

Pushing the boundaries.

Enjoying the freedom on the roads, the horizon in front of you and knowing that the only goal is to have a good time. Now that's even easier with Exide's high-performance batteries. The most advanced components and materials ensure long reliability and durability. Best of all, they're perfect for motorcycles, scooters, jet skis, and a host of other vehicles.



Exide Li-Ion

- Ultra lightweight – up to 80% lighter than lead-acid batteries
- Super-fast recharging
- Extreme cycle life > 2,000 cycles
- Ready to use and maintenance free – just install and forget
- Multi-position mounting – even upside down
- Very low self-discharge – long shelf life and perfect for seasonal use
- State-of-charge indicator for regular checks at one glance
- Covers the majority of parc – spacers included for more fitment options
- First-class safety features



Exide GEL

- Brilliant performance even when partially discharged, prolonging cycle life
- Maximum safety and highly vibration-resistant – easily handles rough road conditions
- Ready to use, no initial acid filling
- Maintenance free – no water refilling
- Very low self-discharge – perfect for seasonal use
- Deep-discharge protection – up to 24 months store without loss in cycle life
- Latest original equipment technology
- Made in Europe



Exide AGM Ready

- Ready to use, no initial acid filling
- Maximum power
- Extended cycle life
- Ideal for cold weather
- Ultra safe and highly vibration-resistant – ideal for rough road conditions
- Maintenance free – no water refilling
- Low self-discharge – suitable for seasonal use
- Original equipment experience inside
- Largest range in the market – covering 80% of the parc



Exide AGM

- Extended cycle life
- Ideal for seasonal use and cold weather
- Great safety features and vibration resistance
- Maintenance free – no water refilling
- 6-bottle acid pack included for initial filling
- Easy stock handling – no recharge required before acid filling
- Wide range covering 90% of the parc around 90% of car parc



Exide Conventional

Exide Conventional batteries are designed for entry-level and older vehicles with basic power needs. They are also ideal for small lawn movers and garden machines.

- Acid pack included for initial filling
- Easy stocking and handling – no recharge required before initial acid filling
- A great variety of battery types, including 6V



New European legislation prohibiting sale of battery electrolyte to end users.

Since February 2, 2021, a new European Regulation (Regulation EU 2019/1148) bans the sale of battery electrolyte to end users since it contains sulphuric acid. Retailers are no longer allowed to supply end users with separate sulphuric acid packs or bottles for the activation of dry, pre-charged batteries. Motorcycle batteries already factory-filled, like Exide GEL and Exide AGM Ready, are not affected by the Regulation. Exide AGM (Dry) and Conventional batteries therefore must be filled and prepared by retailers before being given to the end user.



For detailed filling instructions please scan QR code!

Exide motorcycle batteries type list

Code	Energy (Wh)	CCA A (EN)	L (mm)	W (mm)	H (mm)	Polarity	Terminal type		
							Front	Side	Top

Li-Ion

ELTZ5S	24	120	113	70	85				
ELTZ7S	28.8	150	113	70	85				
ELTX9	36	180	150	87	105				
ELT9B	36	190	150	65	92				
ELTX12	42	210	150	87	93				
ELTZ10S	48	230	150	87	93				
ELTX14H	48	240	150	87	93				
ELT12B	60	260	150	65	130				
ELTZ14S	60	290	150	87	93				
ELTX20H	84	380	175	87	130				

Code	Capacity (10h) Ah	CCA A (EN)	L (mm)	W (mm)	H (mm)	Polarity	Terminal type		
							Front	Side	Top

GEL 12V

GEL12-14	14 (20h)	150	150	87	145				
GEL12-16	16 (20h)	100	180	75	165				
GEL12-19	19 (20h)	170	185	80	170				
GEL12-30	30 (20h)	180	197	132	186				

AGM Ready 12V

AGM12-4	3	50	113	70	85				
AGM12-5	4	70	113	70	105				
AGM12-6	6	90	150	87	93				
AGM12-7	6	100	113	70	105				
AGM12-7F	7	85	150	65	100			4.8	
AGM12-7.5	8	120	150	87	105				
AGM12-8	8.6	145	150	87	93				
AGM12-9	9	120	135	75	139				
AGM12-10	10	150	150	87	130				
AGM12-11	11.2	205	150	88	110				
AGM12-12	12	200	150	90	145				
AGM12-12F	12	150	150	100	100			4.8	
AGM12-12M	12	200	150	90	145				
AGM12-14	12	210	134	89	164				
AGM12-16	16	170	150	90	160				
AGM12-19	18	270	175	87	155				
AGM12-19.1	18	270	175	87	155				
AGM12-18	18	250	181	77	167				
AGM12-23	21	350	205	86	162				
AGM12-31	30	430	166	126	175				

AGM 12V

ET4B-BS	2.3	35	113	38	85				
ETR4A-BS	2.3	35	113	48	85				
ETX4L-BS	3	50	113	70	85				
ETX5L-BS	4	70	113	70	105				
ETX7A-BS	6	90	150	87	93				
ETX7L-BS	6	100	113	70	130				
ETZ7-BS	6	100	113	70	105				
ET7B-BS	6.5	85	150	65	93				
ET9B-BS	8	110	150	70	105				
ETX9-BS	8	120	150	87	105				
ETZ10-BS	8.6	145	150	87	93				
ETX9C-BS	9	120	135	75	139				
ET12A-BS	9.5	130	150	87	105				
ET12B-BS	10	160	150	70	130				
ETX12-BS	10	150	150	87	130				
ETZ14-BS	11.2	205	150	87	110				

Code	Capacity (10h) Ah	CCA A (EN)	L (mm)	W (mm)	H (mm)	Polarity	Terminal type		
							Front	Side	Top

AGM 12V

ET14B-BS	12	190	150	70	145				
ETX14-BS	12	200	150	87	145				
ETX14L-BS	12	200	150	87	145				
ETX14AH-BS	12	210	134	89	164				
ETX14AHL-BS	12	210	134	89	164				
ETX16-BS	14	215	150	87	161				
ETX20H-BS	18	270	175	87	155				
ETX20HL-BS	18	270	175	87	155				
ETX20CH-BS	18	230	150	87	161				
ETX24HL-BS	21	350	205	87	162				

Conventional 6V

6N4B-2A	4	35	101	47	95				Leads
6N6-3B-1	6	40	98	56	110				
6N11A-1B	11	95	121	59	131				
6N12A-2D	12	100	155	56	115				

Conventional 12V

EB4L-B	4	50	120	70	92				
12N5-3B	5	40	120	60	130				
EB5L-B	5	65	120	60	130				
12N5,5-3B	5.5	45	135	60	130				
12N7-3B	7	75	135	75	133				
EB7C-A	8	90	130	90	114				
EB7A	8	85	135	75	133				
EB7L-B	8	85	135	75	133				
12N9-3B	9	85	135	75	139				
12N9-4B-1	9	85	135	75	139				
EB9-B	9	100	135	75	139				
EB10L-A2	11	130	135	90	145				
EB10L-B	11	130	135	90	145				
EB10L-B2	11	130	135	90	145				
12N12A-4A-1	12	115	134	80	160				
EB12A-A	12	165	134	80	160				
EB12AL-A	12	165	134	80	160				
EB12AL-A2	12	165	134	80	160				
12N14-3A	14	130	134	89	166				
EB14-A2	14	145	134	89	166				
EB14-B2	14	145	134	89	166				
EB14L-A2	14	145	134	89	166				
EB14L-B2	14	145	134	89	166				
EB16AL-A2	16	175	205	70	162				
EB18L-A	18	190	180	90	162				
EB16-B	19	190	175	100	155				
EB16CL-B	19	190	175	100	175				
EB16L-B	19	190	175	100	155				
12Y16A-3A	20	210	185	81	170				
E50-N18L-A	20	260	205	90	162				
E50-N18L-A3	20	260	205	90	162				
12N24-3A	24	220	184	124	175				
12N24-4A	24	220	184	124	175				
U1-9	24	240	196	130	180				
E60-N24-A	28	280	184	124	169				
E60-N24AL-B	28	280	184	124	169				
E60-N24L-A	28	280	184	124	169				
E60-N30-A	30	300	185	128	168				
E60-N30L-A	30	300	185	128	168				
E60-N30L-B	30	300	185	128	168				
EB30L-B	30	300	165	130	176				
U1R-11	30	300	196	130	180				