

Range: **LITIO GOLF**

Type name: **DB22LG**



PERFORMANCES*		CONFIGURATION	
Voltage:	12,8 V	Size:	168x128x102 mm
Capacity:	22 Ah (20h)	Polarity:	0
Cap. 5/10/100h:	19/20/23 Ah	Terminal:	CO (connector)
Energy at 100h:	2,94 kWh	Holddown:	-
Cycles at 50%:	>4000	Ventilation:	Sealed
Max. current:	25 A (5seg)	Maintenance:	Not required (MF)
Int. Resistance:	40 mΩ		
Self-Discharge:	15 months		
(from the date of production, at 25°C)			

\*According to standards IEC 60254/60896

INTERNAL CONSTRUCTION		COMPONENTS	
Technology:	Lithium-Ion (LiFePO4) with internal BMS	Container:	ABS/black
Alloy:	Lithium	Lid:	ABS/green
Separator:	Glass mat	Plugs:	Termal sealing, ABS/green
Total Weight:	2,9 kg	Handles:	-
Origin:	Asia		

RECOMMENDATIONS	
Storage:	Check voltage every 10 months.
Recharge:	Use the charger provided with the battery. Avoid temperatures >45°C.
Installation:	Use the cable provided with the battery.

### TABLES & CHARTS

### LITIO GOLF

### DB22LG

